

LEITZ PRIME



Ernst Leitz Wetzlar GmbH
Am Leitz-Park 2 | 35578 Wetzlar | Germany
www.leitz-cine.com | cc@leitz-cine.com

All information subject to change



LEITZ PRIME

TECHNICAL SPECIFICATIONS

Focal Length (mm)	18	21	25	29	35	40	50	65	75	100	135	180
Aperture	T1.8											T2
Image Circle	46.5 mm											
Close Focus (ft)	1'2"	1'10"	1'10"	1'2"	1'6"	1'2"	1'7"	2'2"	2'6"	3'11"	3'11"	4'11"
Close Focus (m)	0.35	0.55	0.55	0.35	0.45	0.35	0.47	0.65	0.75	1.2	1.2	1.5
Horizontal angle of view "Full Frame" 36 mm x 24 mm	90.0°	81.2°	71.5°	63.7°	54.4°	48.5°	39.6	31.0°	27.0°	20.4°	15.2°	11.4°
Horizontal angle of view "Super 35" 24.9 mm x 18.7 mm	69.3°	61.3°	52.9°	46.5°	39.1°	34.6°	28.0°	21.7°	18.8°	14.2°	10.5°	7.9°
Weight (lb)	7.1	6.1	6.2	5.9	6.3	6.0	6.0	6.1	6.2	6.1	6.4	6.8
Weight (kg)	3.2	2.76	2.8	2.67	2.87	2.71	2.7	2.78	2.83	2.77	2.89	3.1
Length (in/mm)	7.9" / 201.5	7.2" / 183.7										7.9" / 201.5



Lens Mount	PL, LPL with Cooke/i
Front Diameter	114 mm
Front Filter Rear Filter	M 112 mm x 1.5 mm screw-in Via net holder
Matched Focus/Iris Ring Locations	All focal lengths
Focus Rotation Iris Rotation	270° (except 18 mm 207°) 66° (except 18 mm 63°)
Focus Scales	Turnable scales, easy change from imperial to metric
Iris Blades Iris Shape	15 Blades Circular through all stops
Color Matching	Matched with LEITZ ZOOM lenses