We use cookies to provide you with the best possible experience in your interactions with Canon and on our website – find out more about our use of Cookies and change your cookie settings <u>here</u>. You agree to our use of cookies on your device by continuing to use our website or by clicking <u>I Accept</u>.

 \times



Canon Sumire Prime Series Specifications

Page by category

Back to product overview

Specifications

Cinematic look Sumire Prime Refined 'cinematic look' named Sumire Prime



Full-Frame coverage With interchangeable PL to EF mount



11-blade diaphragm For attractive bokeh



Warm colour tone Unified with Canon's Cine Lens family

Specifications in detail

Specification

Mount

PL Mount (Interchangeable to EF at authorized service facility)

Focal Length

CN-E14mm T3.1 FP X: 14 mm

CN-E20mm T1.5 FP X: 20 mm

CN-E24mm T1.5 FP X: 24 mm

CN-E35mm T1.5 FP X: 35 mm

CN-E50mm T1.3 FP X: 50 mm

CN-E85mm T1.3 FP X: 85 mm

CN-E135mm T2.2 FP X: 135 mm

T Stop

CN-E14mm T3.1 FP X: T 3.1

CN-E20mm T1.5 FP X: T 1.5

CN-E24mm T1.5 FP X: T 1.5

CN-E35mm T1.5 FP X: T 1.5

CN-E50mm T1.3 FP X: T 1.3

CN-E85mm T1.3 FP X: T 1.3

CN-E135mm T2.2 FP X: T 2.2

Number of iris blades 11 Blades

Angle of view

At 1.5:1

Screen dimensions 36.0×24.0mm

CN-E14mm T3.1 FP X: 104.3° × 81.2°

CN-E20mm T1.5 FP X: 84.0° × 61.9°

CN-E24mm T1.5 FP X: 73.7° × 53.1°

CN-E35mm T1.5 FP X: 54.4° × 37.8°

CN-E50mm T1.3 FP X: 39.6° × 27.0°

CN-E85mm T1.3 FP X: 23.9° × 16.1°

CN-E135mm T2.2 FP X: 15.2° × 10.2°

At 1.78:1

Screen dimensions 24.6×13.8mm

CN-E14mm T3.1 FP X: 82.6° × 52.5°

CN-E20mm T1.5 FP X: 63.2° × 38.1°

CN-E24mm T1.5 FP X: 54.3° × 32.1°

CN-E35mm T1.5 FP X: 38.7° × 22.3°

CN-E50mm T1.3 FP X: 27.6° × 15.7°

CN-E85mm T1.3 FP X: 16.5° × 9.3°

CN-E135mm T2.2 FP X: 10.4° × 5.9°

Minimum Object Distance (from sensor)

CN-E14mm T3.1 FP X: 0.20 m / 8"

CN-E20mm T1.5 FP X: 0.3 m / 12"

CN-E24mm T1.5 FP X: 0.3 m / 12"

CN-E35mm T1.5 FP X: 0.3 m / 12"

CN-E50mm T1.3 FP X: 0.45 m / 18"

CN-E85mm T1.3 FP X: 0.95 m / 3'2"

CN-E135mm T2.2 FP X: 1.0 m / 3'3"

Object Dimensions at M.O.D.

Aspect ratio 1.5:1

Screen dimensions 36.0x24.0mm

CN-E14mm T3.1 FP X: 25.2 × 16.8 cm

CN-E20mm T1.5 FP X: 33.8 × 22.5 cm

CN-E24mm T1.5 FP X: 28.8 × 19.2 cm

CN-E35mm T1.5 FP X: 20.2 × 13.5 cm

CN-E50mm T1.3 FP X: 25.0 × 16.7 cm

CN-E85mm T1.3 FP X: 34.4 × 22.9 cm

CN-E135mm T2.2 FP X: 21.1 × 14.1 cm

Aspect ratio 1.78:1

Screen dimensions 24.6x13.8mm

CN-E14mm T3.1 FP X: 17.2 × 9.7 cm

CN-E20mm T1.5 FP X: 23.1 × 13.0cm

CN-E24mm T1.5 FP X: 19.7 × 11.0 cm

CN-E35mm T1.5 FP X: 13.8 ×7.7 cm

CN-E50mm T1.3 FP X: 17.1 × 9.6cm

CN-E85mm T1.3 FP X: 23.5 × 13.2 cm

CN-E135mm T2.2 FP X: 14.4 × 8.1 cm

Front diameter Φ114 mm

Approx. Size (W×H×L) CN-E14mm T3.1 FP X: 118.4 × 118.4 × 86.0 mm CN-E20mm T1.5 FP X: 118.4 × 118.4 × 93.5 mm CN-E24mm T1.5 FP X: 118.4 × 118.4 × 93.5 mm CN-E35mm T1.5 FP X: 118.4 × 118.4 × 93.5 mm CN-E50mm T1.3 FP X: 118.4 × 118.4 × 93.5 mm CN-E85mm T1.3 FP X: 118.4 × 118.4 × 93.5 mm

Approx. Mass

CN-E14mm T3.1 FP X: 1.2 kg

CN-E20mm T1.5 FP X: 1.2 kg

CN-E24mm T1.5 FP X: 1.2 kg

CN-E35mm T1.5 FP X: 1.1 kg

CN-E50mm T1.3 FP X: 1.1 kg

CN-E85mm T1.3 FP X: 1.3 kg

CN-E135mm T2.2 FP X: 1.4 kg

Gear Pitch: 0.8

Focus Dia.: 116.8 mm

Zoom Dia.: N.A.

Iris Dia.: 100.8 mm

More ways to shop: visit the Canon Store or find a reseller.

Copyright 2019. All Rights Reserved.